
PTFE hoses for Food- and Sterile technique


PTFE corrugated hose, braided, spiral



DN*	A	B	C	Pressure bar, 20 °C	Vacuum bar, 20 °C			Art.No	EUR
15	19	9,5 **	1	41	0,8			6124-9,5x1	**Enquiry**
20	25	14,3 **	1,25	35	0,8			6124-14,3x1,25	**Enquiry**
25	32	20,6 **	1,65	31	0,8			6124-20,6xX1,65	**Enquiry**
32	38	25,4 **	1,65	27	0,8			6124-25,4x1,65	**Enquiry**

– Minimum order quantity 1m – Only available with hose nozzles ready-for-use. Also anti-static available with conductive black PTFE. The hoses are also available with PTFE ined hose nozzles that will be beaded on the sealing surface. * nominal size / ** real size, inner-Ø between waves


PTFE corrugated hose, waveless, braided, flexible



DN	A	B	C	Pressure bar, 20 °C	Vacuum bar, 20 °C			Art.No	EUR
10	12,8	9,5	-	80	0,8			6128-9,5	**Enquiry**
13	17,8	13,5	-	70	0,8			6128-13,5	**Enquiry**
15	21,6	16,5	-	65	0,8			6128-16,5	**Enquiry**
20	24,4	19,8	-	60	0,8			6128-19,8	**Enquiry**
25	31,9	26,1	-	50	0,8			6128-26,1	**Enquiry**
32	39,5	32,5	-	45	0,8			6128-32,5	**Enquiry**
38	46,7	38,8	-	40	0,8			6128-38,8	**Enquiry**
50	60,7	51,5	-	30	0,8			6128-51,5	**Enquiry**

– Minimum order quantity 1m – Only available with hose nozzles ready-for-use. Also anti-static available with conductive black PTFE. The hoses are also available with PTFE ined hose nozzles that will be beaded on the sealing surface.


PTFE corrugated hose, waveless, braided



DN	A	B	C	Pressure bar, 20 °C	Vacuum bar, 20 °C			Art.No	EUR
13	15,8	11,5	-	50	-			6132-11,5	**Enquiry**
16	20,8	15,5	-	50	-			6132-15,5	**Enquiry**
19	23,6	18,5	-	60	-			6132-18,5	**Enquiry**
25	27,7	22,8	-	40	-			6132-22,8	**Enquiry**
32	36,8	30,5	-	45	-			6132-30,5	**Enquiry**
38	43,1	36,6	-	40	-			6132-36,6	**Enquiry**
50	55,2	48,5	-	25	-			6132-48,5	**Enquiry**

– Minimum order quantity 1m – Only available with hose nozzles ready-for-use.

PTFE corrugated hose, waveless, braided, silicone cover



DN	A	B	C	Pressure bar, 20 °C	Vacuum bar, 20 °C			Art.No	EUR
6	11,6	6,4	-	130	0,8			6126-6,4	**Enquiry**
10	15,5	9,5	-	100	0,8			6126-9,5	**Enquiry**
13	19,5	12,7	-	70	0,8			6126-12,7	**Enquiry**
20	27,3	19	-	60	0,8			6126-19	**Enquiry**
25	34,8	25,4	-	50	0,8			6126-25,4	**Enquiry**

– Minimum order quantity 1m – Only available with hose nozzles ready-for-use. Also anti-static available with conductive black PTFE.

LINNEMANN
Rohrverbindungen • Edelstahlarmaturen
Pipe connections • Stainless steel fittings

LINNEMANN GmbH • Heerweg 14–16
72070 Tübingen / Germany

Fon: +49 (0) 7071 97555-0
Fax: +49 (0) 7071 97555-10

E-Mail: info@linnemann-online.com
Internet: www.linnemann-online.com